



# Polyester Eye & Eye Flat Web Sling Technical Specs.



**Flat Web Sling Capacity**

- \* Polyester Webbing stretch: Approx. 7% at full capacity.
- \* Prolonged exposure to UV / sunlight will degrade Polyester webbing.
- \* Polyester webbing starts to degrade at temperatures above 194°F.
- \* Fabricated with either Twisted eyes (TE) or Flat eyes (EE).
- \* Slings 3" and wider are fabricated with tapered eyes.
- \* Available in Scuff Edge material, 1" through 4"

**Length Tolerance:**

Sling	Type Tolerance
1 Ply	+/- 1.5" + 1.5% of length
2 Ply	+/- 2.0" + 2.0% of length
3 Ply	+/- 3.0" + 3.0% of length
4 Ply	+/- 3.0" + 3.0% of length

**Distributed by:**



**INDUSTRIAL GROUP**

[www.pssigroup.com](http://www.pssigroup.com)

	<u>Vertical</u>	<u>Choker</u>	<u>Basket</u>	<u>Min Length</u>
<b>E191</b> - 1,600	1,250	3,200	3 ft	
<b>E192</b> - 3,200	2,500	6,400	4 ft	
<b>E193</b> - 4,800	3,800	9,600	4 ft	
<b>E194</b> - 6,400	5,000	12,800	4 ft	
<b>E196</b> - 9,600	7,700	19,200	5 ft	
<b>E198</b> - 12,800	10,200	25,600	6 ft	
<b>E291</b> - 3,200	2,500	6,400	3 ft	
<b>E292</b> - 6,400	5,000	12,800	3 ft	
<b>E293</b> - 8,600	6,900	17,200	4 ft	
<b>E294</b> - 11,500	9,200	23,000	4 ft	
<b>E296</b> - 16,300	13,000	32,600	6 ft	
<b>E298</b> - 19,200	15,400	38,400	6 ft	
<b>E2910</b> - 22,400	17,900	44,800	7 ft	
<b>E2912</b> - 26,900	21,500	53,800	8 ft	
<b>E391</b> - 4,100	3,300	8,200	4 ft	
<b>E392</b> - 8,300	6,600	16,600	4 ft	
<b>E393</b> - 12,500	10,000	25,000	5 ft	
<b>E394</b> - 16,000	12,800	32,000	5 ft	
<b>E491</b> - 5,000	4,000	10,000	4 ft	
<b>E492</b> - 10,000	8,000	20,000	4 ft	
<b>E493</b> - 14,900	11,900	29,800	5 ft	
<b>E494</b> - 19,800	15,800	39,600	5 ft	



Scan QR code to visit our website

